

# Travelstar™ 5K1000

2.5-Inch Mobile 5400 RPM  
9.5mm Hard Disk Drives

## Highlights

- Up to 1TB<sup>1</sup> of capacity
- Advanced Format, 512 byte emulation
- 6Gb/s SATA interface
- Low power consumption
- Halogen-free for eco-friendly design
- Self-encrypting models for data security
- Enhanced availability (EA) models for applications needing around-the-clock access in lower-transaction environments

## Applications/Environments

- Notebook PCs
- External storage
- Gaming consoles
- Small-form-factor video devices
- Blade servers (EA)
- Network routers (EA)
- Video surveillance (EA)

## 1TB of Storage Capacity for Mobile Platforms

Travelstar™ 5K1000 is a 5400 RPM, 500GB/platter, 2.5-inch hard drive available in 640GB, 750GB and 1TB models. This standard 9.5mm, two-disk design, intended for use in notebook PCs, external storage, gaming consoles and other mobile applications, leverages Advanced Format, which increases the physical sector size on hard drives from 512 bytes to 4096 (4K) bytes to increase drive capacities and improve error correction capabilities. Consult the HGST Advanced Format Technology Brief for more information on using these hard drives. The Travelstar 5K1000 is the first 1TB 2.5-inch HDD with a 6Gb/s SATA interface and delivers best-of-breed 5400 RPM performance in PCMark 7 and PCMark Vantage testing. The 5K1000 continues to demonstrate HGST's ecological leadership with its halogen-free design and power-efficient operation, and carries the EcoTrac classification. Travelstar 5K1000 delivers the highest mobile capacity with excellent performance to meet the needs of consumers and commercial users in an eco-friendly, rugged design.

## Encryption Option

Travelstar 5K1000 is the seventh generation self-encrypting drive (SED) to feature HGST's Bulk Data Encryption. The SED encrypts data using protected keys in real time, providing users the highest level of data protection available. It also speeds and simplifies drive re-purposing. By deleting the encryption key, the data on the drive is rendered unreadable, thereby eliminating the need for time-consuming data-overwrite. For information about the SED models designed to the Trusted Computing Group (TCG) Opal Storage Security specification, please contact your HGST representative.

## Enhanced Availability (EA)—for 24x7 Access to Data

HGST provides enhanced availability models of the Travelstar 5K1000 that allow 24x7 access to data to support applications that require round-the-clock operation. The 5K1000 provides high capacity, durability and low power utilization on a proven platform for quality and reliability. EA models support the stringent demands of "always-on" applications in lower-transaction environments.

## Features and Benefits

	Feature / Function	Benefits
<b>Capacity</b>	Up to 1TB storage	Up to 250 hours of high-definition video, 1000 hours of standard video, 350 movies, 250,000 4-min songs or 500 games *
<b>Power</b>	1.6W read/write power 0.5W low power idle	Low energy use and long battery life for more "unplugged" notebook time
<b>Reliability</b>	400G operating shock 1000G non-operating shock	Best protection against bumps and rough handling
	Thermal Fly-height Control (TFC)	Better soft error rate for improved reliability
	TrueTrack™ technology	Tracking accuracy in high shock or vibration environments
<b>Performance</b>	Up to 998Mb/s media transfer rate SATA 6Gb/s interface	Best-of-breed 5400 RPM application performance in PCMark 7 and PCMark Vantage testing
<b>Acoustics</b>	Quiet acoustics	Richer audio-listening experience for music, movies and games
<b>Interface</b>	SATA 3Gb/s	Higher data throughput
<b>Security Option</b>	Bulk Data Encryption	Helps guard against data theft

\* Actual storage may vary depending on the compression rate applied. Capacities may not be combined.



1TB, 750GB and 640GB  
5400 RPM | SATA 6Gb/s



## HGST Quality and Service

HGST Travelstar hard disk drives are designed to the highest quality standards and contain field-proven components. HGST provides worldwide technical support and integration services to enable global customers to bring their products to market quickly.

### How to read the Travelstar model number

HTS727575A9E364 = 750GB, SATA 3Gb/s

H = HGST

T = Travelstar

S = Standard (vs E for Enhanced Availability)

72 = 7200 RPM

10 = Full capacity — 1TB

10 = Capacity this model, 10 = 1TB  
(75 = 750GB, 64 = 640GB)

A = Generation code

9 = 9.5mm z-height

E6 = SATA 6Gb/s with 512 emulation

8 = 8MB cache

0 = No encryption (1 = BDE,

5 = TCG Opal Encryption)

### Information and Technical Support

www.hgst.com (Main Web site)

www.hgst.com/partners (Partner Web site)

#### North America

support\_usa@hgst.com

Toll free: 1 888 426-5214, Direct: 1 408 717-8087

#### Asia Pacific

support\_ap@hgst.com / 65 6840 9595

#### EMEA and UK

support\_uk@hgst.com / 44 20 7133 0032

#### Germany

support\_uk@hgst.com / 49 6929 993601

### Program Support

Partners First Program

channelpartners@hgst.com

## Specifications

Models	Standard Models	EA Models
	HTS541010A9E680	HTE541010A9E680
	HTS541010A9E681	HTE541075A9E680
	HTS541075A9E680	HTE541064A9E680
	HTS541075A9E681	
	HTS541064A9E680	
	HTS541064A9E681	
<b>Configuration</b>		
Interface	SATA 6Gb/s	←
Capacity (GB) <sup>1</sup>	1TB / 750 / 640	←
Sector size (bytes) <sup>2</sup>	512e	←
Recording zones	30	←
Aerial density (max, Gbit/sq.in.)	694	←
<b>Performance</b>		
Data buffer (MB) <sup>3</sup>	8	←
Rotational speed (RPM)	5400	←
Latency average (ms)	5.5	←
Media transfer rate (max, Mbits/sec)	998	←
Interface transfer rate (MB/sec)	600	←
Seek time		
Average (typical) ms (read) <sup>4</sup>	12	←
Track to track (typical) ms (read)	1	←
Full stroke (typical) ms (read)	20	←
<b>Reliability</b>		
Load/Unload cycle	600,000	←
Power on hours (POH) per month	N/A	730
Availability <sup>5</sup>	N/A	24x7
<b>Power</b>		
Requirement	+5VDC (+-5%)	←
Dissipation		
Startup (W, peak, max)	4.5	←
Seek (W, avg.)	1.8	←
Read/Write (W, avg.)	1.6	←
Performance idle (W, avg.)	1.5	← Idle (Avg.)
Active idle (W, avg.)	0.8	N/A
Low power idle (W, avg.)	0.5	N/A
Standby (W, avg.)	0.2	←
Sleep (W)	0.1	←
<b>Physical size</b>		
Height (max, mm)	9.5	←
Dimensions (width x depth, mm)	70 x 100	←
Weight (max, g)	102	←
<b>Environmental (operating)</b>		
Shock (half-sine wave)	400G/2ms, 225G/1ms	←
Ambient temperature	0° to 60° C	←
<b>Environmental (non-operating)</b>		
Shock (half-sine wave)	1000G/1 ms	←
Ambient temperature	-40° to 65° C	←
<b>Acoustics (A-weighted sound power)</b>		
Idle (Bels, typical)	2.4	←
Seek (Bels, typical)	2.6	←

<sup>1</sup> One GB is equal to one billion bytes and one TB equals 1,000GB (one trillion bytes) when referring to hard drive capacity. Accessible capacity may be less. Lower capacity models may not be available in all markets.

<sup>2</sup> Advanced Format drive: 4K physical sectors with 512 byte emulation

<sup>3</sup> Portion of buffer used for firmware

<sup>4</sup> Excludes command overhead

<sup>5</sup> Designed for low duty cycle, non mission-critical applications in PC, nearline and consumer electronics environments, which vary application to application

