

Optimo Style 16-40

Lightweight Series



TECHNICAL SPECIFICATIONS :

Zoom Ratio:	2.5X
Focal Length:	16 - 40 mm
Aperture:	f/2.6 – T2.8
MOD:	2 ft – 0.6 m
Internal Focus:	Yes
Image Coverage:	S35+; 31.4 mm diagonal
Weight (approx.):	4.2 lbs – 1.92 kg
Length:	186 mm
Front Diameter:	114 mm

- . Extremely fast aperture of T2.8 with no ramping
- . 320° focus rotation with over 20 precise focus witness marks and no breathing
- . Optical design optimized for today's large format single sensor middle budget cameras with extended compatibility
- . Calibrated focus marks in feet or meters
- . Optimo quality and cinematic look at an affordable price
- . Available in PL mount. PV, Nikon and Canon mounts available on request
- . Expanded capabilities with Optimo 2x and 1.4x range extenders

CAN BE OFFERED WITH OPTIONAL ANGENIEUX SERVO UNIT (ASU) :



WEIGHT :
1.5 lbs - 0.7 kg
WEIGHT WITH OPTIMO STYLE
16-40 / 30-76 :
5.7 lbs - 2.62 kg

- Provides control of zoom, focus and iris
- Is compatible with Broadcast remote handles and Cinema remote control
- F/T/Z can be remotely controlled via various wired/ wireless devices: Preston, Angénieux and more to come based on customer demands
- Generates lens metadata based on Cooke protocol

AVAILABLE ACCESSORIES :



DSLR Mounts Extender 1.4 & 2 X Wide Angle 0.75X

FIELD OF VIEW FOR 35mm ACADEMIC (22x16 mm) :

Focal Length:	16 mm	40 mm
Horizontal angular field of view:	69°	31.2°
Object dimensions at MOD (mm):	569x408	230x170



A - external connector
B - remote connector
C - camera interface
D - main power supply