



42-051



42-054



42-053

42-052

## SCHURTER IEC (CEE22) AC MAINS POWER CONNECTORS

IEC AC mains power connectors, non keyed (cold condition), 10 amp 250VAC 50/60Hz rated. Approvals: IEC/EN, UL, AS/NZS and CSA.

### Cable Types

Rewireable male and female cable types with professional screw terminals (wire receptacle hole and cross clamp-screw). Wire size up to 3x1mm sq. (18 AWG).

### Panel Types

#### Snap-in type, 42-052

Male (power inlet) snap-in type. Suitable for 1.5mm panel thickness. 6.3mm, Quick connect 'Faston' connection.

Panel cutout 27.5 +0.2/-0.0 x 19.8mm +0.2/-0.0.

#### Flange type, 42-053

Male (power inlet) two hole flange type. 6.3mm, Quick connect 'Faston' connection. Panel cutout 27.5 x 20.0mm min, screw hole centres 40.00mm, 3.5mm diameter.

Optional accessories: Moulded PVC insulating cover, stock code 42-159.

### Alternatives

Right angled cable types, fused inlet and snap-in types for other panel thicknesses are available to special order, please contact Sales.

42-051	SCHURTER AC MAINS POWER CONNECTOR, IEC Female, cable
42-054	SCHURTER AC MAINS POWER CONNECTOR, IEC Male, cable
42-052	SCHURTER AC MAINS POWER CONNECTOR, IEC Male, panel 1.5mm, snap-in
42-053	SCHURTER AC MAINS POWER CONNECTOR, IEC Male, panel, flange, 2 hole
42-159	CANFORD REAR INSULATING COVER For IEC panel connector

UK Sales - tel 0191 418 1122  
 fax 0191 418 1123  
 sales@canford.co.uk

International Sales - tel +44 191 418 1133  
 fax +44 191 418 1134  
 international@canford.co.uk

Tech Support - tel 0191 418 1144  
 fax 0191 418 1145  
 techsupport@canford.co.uk