



**Sales Start Date:** Dec 2012

**Target Market:** A fast 35mm prime lens for photographers shooting hand held in low light.

### Key Features:

- Superb image quality from a fixed 35mm focal length prime lens
- Image Stabilizer enables hand-held photography with shutter speeds up to four stops slower than normal without camera shake
- Fast f/2 maximum aperture enables low-light shooting and shallow depth-of-field photography
- Fast, near-silent AF tracks moving objects with speed and accuracy. Full-time manual override allows instant fine adjustment
- Compact, lightweight design you can take everywhere
- Nine-bladed circular aperture for smooth out-of-focus bokeh
- Moulded glass aspherical lens element corrects aberrations
- 0.24m minimum focusing distance

### Power to see things differently

A 35mm prime lens with a four-stop Image Stabilizer and f/2 maximum aperture – ideal for low-light photography. Ultrasonic AF is fast and accurate. An aspherical lens element boosts image quality.

Product Name	Mercury Code	EAN Code	Recommended Retail Price
<b>EF 35mm f/2 IS USM</b>	5178B005AA	4960999845791	£799.99 / €1029.99
<b>What's in the box:</b> EF 35mm f/2 IS USM, Lens cap E-67II, Lens dust cap E, Instruction manual, Warranty card (EUR)			

Accessories	Mercury Code	EAN Code
Lens case LP1116	2780A001AA	4960999470757
Lens Hood EW-72	5185B001AA	4960999780665

## Technical Specifications

# EF 35mm f/2 IS USM

<b>OPTICAL FEATURES/SPECIFICATIONS</b>	
Image size	-
35mm film equivalent focal length (mm)	-
Angle of view (horizontal, vertical, diagonal)	63°, 38°, 54°
Lens construction (elements/groups)	10/8
No. of diaphragm blades	8
Minimum aperture	22
Closest focussing distance (m)	0.24
Maximum magnification (x)	0.24
Distance Information	Provided
Image stabilizer	4 stops
AF actuator	Ring USM <sup>3</sup>
<b>PHYSICAL SPECIFICATIONS</b>	
Dust/moisture resistance <sup>a</sup>	-
Filter diameter (mm)	67
Max. diameter x length (mm)	77.9 x 62.6
Weight (g)	335
<b>ACCESSORIES</b>	
Lens Cap	E-67 II
Lens hood	EW-72
Lens case/pouch	LP1116
Maximum number of Hood III compatible with Gelatin Filter Holder III	1
Maximum number of Hood IV compatible with Gelatin Filter Holder IV	1
Magnification with Extension Tube EF12 II	0.60-0.36
Magnification with Extension Tube EF25 II	1.04-0.79
Extender Compatibility	Not compatible
Other Accessories	-
<b>SPECIFICATIONS WITH EF 1.4X II</b>	
Focal Length	-
Maximum Aperture	-
Maximum Magnification	-
AF Possible	-
IS	-
<b>SPECIFICATIONS WITH EF 2X II</b>	
Focal Length	-
Maximum Aperture	-
Maximum Magnification	-
AF Possible	-
IS	-

- Image Circle Ø67.2mm
- Minimum aperture if using 1/3stop increments
- Full time Manual focus
- Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.
- Not compatible at wide angles
- Use the rear drop in filter holder
- Gelatin Filter Holder Adapter III required
- Use 52mm drop in filter holder
- When used with EF 50mm f/2.5 Compact Macro
- Vignetting occurs during Tilt and Shift
- AF possible with EOS-1 series only
- IS will not work with the following cameras EOS-1, EOS 5, EOS 100, EF-M, EOS 1000/F/n/Fn, EOS 700, EOS 10, EOS RT, EOS 600/630, EOS 850, EOS 750, EOS 620, EOS 650

## Logistics Information

Pack Description	Quantity	Dimensions (L x W x H in mm)	Weight (Net / Gross in kg)
Individual	1	137 x 137 x 134	0.423/0.554
Carton	6	432 x 294 x 223	2.98/3.98
Pallet	144	1200 x 800 x 1042	-/97.8