

HF40

Helia 40 Watt Bi-Color LED Fresnel Light

ONE SHEET

Overview

The Helia Bi-Color LED light offers the flexibility of color temperatures ranging from 2700K to 5600K for any shooting situation.

The 4-inch Fresnel lens can focus from 60-degree flood to 15-degree spot. With a high CRI and TLCI, the Helia gives shooters all the color they're looking for and more. The large digital display allows you to move through the menus and tweak settings with ease. The flicker feature can be tuned to any frequency.

The HF40 light can be powered with a pro battery and comes with a V-mount battery plate and DC cable. It also comes with barn doors and AC power cable.



HF40 | Helia 40 Watt Bi-Color LED Fresnel Light | **UPC Code:** 847983014453

Special Features

- Bi-Color Light adjustable from 2700K-5600K
- 4" Fresnel with flood to spot
- High CRI and TLCI
- Can be powered by Pro V-Mount Battery
- Flicker feature allows slow to fast strobe
- Large digital readout for easy adjustment
- Long LED Lifespan
- Barn Doors Included

Recommended For

- Studio Lighting
- Interviews

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

HF40

Features you need, Prices you want.

Adjustable Bi-Color Light

Bi-Color light can be adjusted simply by turning the knob and dialing in the correct color temperature.

Spot to Flood Fresnel

Spot-to-flood adjustment.

Battery Options

Pro Battery options available.

Large Digital Readout

The large LCD Screen allows you to see all menu settings when making changes.

Flicker Feature

The flicker setting allows for special effect lighting or for dialing in the flicker frequency for camera speed.

What's Included

- 1 x 40 Watt Light Fixture
- 1 x 6 Ft Power Cable
- 1 x Barn Door
- 1 x Light Stand
- 1 x P-TAP Cable
- 1 x V-Mount Plate
- 1 x Yoke



Accessories

- KCP-703** Stage Clamp w/ 16mm Stud
- SW-04** Safety Wire
- MK350** Spectrometer from UPRtek
- IDX-1204** 12 Channel DMX Console
- IDX-096** 96 Channel DMX Console

Specifications

| | |
|----------------------|---|
| Beam Angle | 18°-60° Angle |
| Build Material | Aluminum |
| Control | Toggle Button w/ Knob |
| Cooling System | Active Cooling Fan |
| Dimming | Flicker-Free, Onboard, 100%-0% |
| Fixture Size | 8.5 x 7.5 x 13 In. |
| Fixture Weight | 5 Lbs |
| Focusing | Rotating Rear Knob |
| Foot Candles (Flood) | 5ft:214.5 fc / 10ft:44.77 fc / 15ft:19.04 fc |
| Foot Candles (Spot) | 5ft:1227.2 fc / 10ft:264.7 fc / 15ft:108.9 fc |
| Head Type | 2700-5600K |
| Lens | 4" Glass Fresnel |
| Light Source | 1x40 watt LED Bi-Color |
| LUX (Flood) | 1m:2309 lux / 3m:482 lux / 5m:205 lux |
| LUX (Spot) | 1m:13210 lux / 3m:2850 lux / 5m:1173 lux |
| Power Supply | 6 Ft. Power Cable |
| Rating | AC volts 120volts AC, 50-60Hz, 40 watts |
| Yoke | Cast Aluminum w/ 1 1/8" Pin |
| Shipping Dimensions | 33 x 22 x 13 In. / 83.8 x 55.8 x 33 cm |
| Shipping Weight | 25 Lbs / 11.33 kg |

Photometrics



Photometrics available in foot candles online at www.ikancorp.com



ikan

Houston, Texas

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com