

# LB-2F1H

Lyra Bi-Color 3-Point LED Soft Panel Light Kit w/ 2x LB10 + 1x LB5

ONE SHEET

## Overview

Ikan introduces the new brand of Lyra Soft Lights! What you can expect when high CRI LED Chips combine with a soft panel is a beautiful, soft wrapping light. What's unique about a Lyra soft light is how it creates a nice, clean shadow. The Lyra Bi-Color Soft Panel Half x 1 LED Light is equivalent to a 350-Watt incandescent soft light.

The soft light's bi-color adjustability ranges from 3200K-5600K & works well with any lighting production. Its brightness is consistent across ALL color temperatures! The 110° wide beam angle can easily light a large area by itself. The 30° yoke, baby 5/8" and junior 1 1/8" combo pin also allows you to configure or attach them to any stand. Additionally, the yoke's strong steel tension knobs can securely lock the light in place at any angle.

One the back, the large yellow control knob lets you adjust the light's brightness & color temperature with just a few simple clicks! The LED readout provides extremely precise measurements for reference. Battery flexibility is guaranteed with Gold & V-Mount pro battery plates included. You can also plug in the Lyra Soft Light practically anywhere thanks to its maximum 40-Watts at 0.3 amps.

Add to that, Ikan's reliable barn doors with intensifiers and you can clearly see why Lyra's Soft Lights are the best value package!



LB-2F1H | Lyra Bi-Color 5-Point LED Soft Panel Light Kit w/ 2x LB10 + 1x LB5 | UPC Code: 847983018321

## Special Features

- High CRI Chip LEDs paired with 1/2 stop soft diffusion panel
- Bi-Color adjustable from 3200K-5600K
- Bright consistent light across all color temperatures
- Beam Angle: 110 degrees
- Clean single shadow without artifacts
- Baby 5/8 inch/Junior 1-1/8 Combo Pin adaptor with right angle receiver hole
- 30 degree angled yoke for unobstructed movement

## Recommended For

- Studio Lighting
- Field Lighting

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



[www.facebook.com/ikanseeit](http://www.facebook.com/ikanseeit)



[www.twitter.com/ikancorp](http://www.twitter.com/ikancorp)



[www.vimeo.com/ikancorp](http://www.vimeo.com/ikancorp)



[www.youtube.com/ikancorp](http://www.youtube.com/ikancorp)

# LB-2F1H

Features you need, Prices you want.

## High Soft Light Combination

The high CRI LED chips and ½-Stop spot diffusion panel can output a strong, bright diffused light.

## Bi-Color Adjustability

The soft light's adjustability ranges from 3200K-5600K and works well with any lighting production.

## Consistent & Bright

Lyra Soft Lights deliver a consistently bright light across all color temperatures at all times.

## 110° Beam Angle

The Lyra Soft Light's wide beam angle provides a large amount of soft light all on it's own.

## Clean Single Shadow

Lyra's Soft Lights create single shadows that produce more of a natural, clean shot.

## Versatile Combo Pin

The Baby 5/8" & Junior 1-1/8" combo pin adapter makes it easy to attach to any grip stand.

## 30° Angled Yoke

The 30° angled yoke provides unobstructed movement of the light.

## Steel Tension Knobs

The new steel tension knobs are built to be stronger and more secure. This allows you to lock the light in at any angle.

## Single Knob Control

A single control knob makes it easy to adjust brightness, or color temperature at any time.

## LED Readout

The new, brighter LED readout provides precise adjustments of light output.

## Gold & V-Mount

Battery flexibility is key when you're on-the-go.

## Barndoors Included

Ikan's reliable barn doors with intensifiers make it much easier to shape the light as needed.

## Maximum Power Draw

The Lyra Soft Light has a maximum power draw of 40-Watts, which allows you to plug into any AC power.

## 350-Watt Equivalent

By comparison, the Lyra Bi-Color Soft Panel Half x 1 LED Light is equivalent to a 350-Watt incandescent soft light.

## RF Remote Control

Controlling multiple light at a distance is possible with the RF remote control.

## LB5 Specs

Light Source	510 0.2 Watt LEDs
Head Type	Bi-Color 3200K-5600K
Lens	½ Stop Soft Diffusion
Beam Angle	110°
Control / Dimming	Knob Control
Build Material	Heavy Duty Resin Plastic
Cooling System	Passive Cooling
Stand Mount	Baby 5/8" & Junior 1-1/8" combo pin
Fixture Size	14 x 8 x 3 In.
Fixture Weight	4 lbs
Power Supply	Input: 110-220 VAC Output: 15VDC @ 5.0A
Yoke	30°

## LB10 Specs

Light Source	900 0.2 Watt LEDs
Head Type	Bi-Color 3200K-5600K
Lens	½ Stop Soft Diffusion
Beam Angle	110°
Control / Dimming	Knob Control
Build Material	Heavy Duty Resin Plastic
Cooling System	Passive Cooling
Stand Mount	Baby 5/8" & Junior 1-1/8" combo pin
Fixture Size	14 x 14 x 3 In.
Fixture Weight	6 lbs
Power Supply	Input: 110-220 VAC Output: 15VDC @ 7.0A
Yoke	30°

## Shipping

Shipping Dimensions (Box 1)	24 x 18 x 18 In.
Shipping Weight (Box 1)	30 lbs
Shipping Dimensions (Box 2)	41 x 9 x 9 In.
Shipping Weight (Box 2)	16 lbs

## What's Included

1 x Half x 1 Light Fixture	3 x HD Light Stand
1 x Light Bag	3 x Power Supply w/ Cable
1 x Stand Bag	3 x Remote Control
2 x 1 x 1 Light Fixture	3 x V-Mount Battery Plate
3 x Gold Mount Battery Plate	3 x Yoke Mount

