



LC-2C

7.4V Two-Channel Simultaneous Charger for Canon Batteries

PROSeries

The LC-2C two channel simultaneous charger is designed to charge Canon 7.4V batteries for professional camcorders.

LC-2C Product Features:

- Compatible with Canon 7.4V batteries—BP-925, 950G, 955, 970G, 975
- Universal AC input for worldwide use.
- Capable of multiple configurations for use as stand alone charger or joint connection to a second LC-2C.
- Automatic safety and protection features include low voltage charging, thermal monitoring and overcharge protection.
- Status LED indicator provides detailed display of charging process and fault detection.
- Charging will automatically stop when the battery is fully charged.
- Standard IDX two-year warranty.



Technical Specification

Input Voltage:

AC Adaptor - 100-240V 60/50Hz automatic
DC Input - DC 14-19V

Power Consumption:

36W maximum

Charge Current:

1.6A

Operating Temperature:

32°F ~ 104°F

Dimensions:

5.51(W) x 1.81(H) x 5.07(D) inches

Weight:

0.58 lbs. without AC adaptor

IDX System Technology, Inc.
19001 Harborage Way, Suite 105
Torrance, CA 90501
U.S.A.
Telephone: (310) 328-2850
Fax: (310) 328-8202



For further information, email us: idx.usa@idx.tv or visit our website www.idxtek.com
IDX reserves the right to change the specifications contained herein without notice.