

New




# FL7000U

**FULL HD 1080** **5000lm**  
HIGH BRIGHTNESS

### Input and Output Terminals

- 1 REMOTE IN and OUT terminals
- 2 LAN terminal
- 3 SERIAL terminal (D-SUB 9-pin)
- 4 USB (COMPUTER) terminal
- 5 COMPUTER/COMPONENT VIDEO DVI-D (HDCP) terminal (DVI-D 24-pin)
- 6 COMPUTER / COMPONENT VIDEO IN 1 terminals (R/Ps, G/Y, B/Ps, H/HV, V) (BNC)
- 7 Main power switch O : OFF 1 : ON
- 8 Power jack
- 9 AUDIO IN 1 terminal (Mini jack)  
— The AUDIO IN 1 terminal is used for both COMPUTER 1 and DVI input.
- 10 AUDIO IN 2 terminal (Mini jack)
- 11 COMPUTER/COMPONENT VIDEO IN 2 terminal (Mini D-SUB 15-pin)
- 12 MONITOR OUT terminal (Mini D-SUB 15-pin)
- 13 AUDIO OUT terminal (Mini jack)
- 14 VIDEO IN and audio input terminals
- 15 S-VIDEO IN and audio input terminals




### Optional Lenses Line-UP



\* For those who already have OL-X500FR, a front cabinet CA-XL6600(FR) is necessary for use.

### Dimensions (unit: mm, inch)



### Specifications

Model	FL7000U
Display technology	1.1" 3-LCD (with micro lens)
Resolution	1920 x 1080 (Total 2,073,600 pixels)
Brightness	5000 ANSI Lumens
Contrast ratio	1000:1 (on/off)
Projection lens	f=51-64mm, F1.8-2.1
Throw ratio	2.01 - 2.56
Offset axis	10 : 0 (default) with variable H + V powered lens shift (excluding OL-X500FR)
Zoom / Focus	Motorized Zoom & Focus
Picture size	60" - 250" (Diagonal)
Source lamp	220W (Shut Off Time 4000Hrs) with Low mode, 275W (Shut Off Time 2000Hrs) with Standard mode
Computer compatibility	Resolution: 640 x 400 (Expand) - 1920 x 1080 (Real) - 1600 x 1200 (Compress) Sync on Green available
Video compatibility	NTSC / NTSC 4.43 / PAL (including PAL-M, N) / SECAM / PAL-60, Component Video: 480i/p (525i/p), 576i/p (625i/p), 720p (750p 50/60Hz), 1080i (1125i 50/60Hz), 1080p (1125p 50/60Hz), (1080i (1250i 50Hz) is not available) SCART (RGB + 1V sync, only Mini D-Sub 15pin Terminal)
Input terminals	PC: 5 BNC x 1, Mini D-Sub 15pin x 1, DVI-D(with HDCP) x 1, PC Audio: Stereo mini jack (φ3.5mm) x 2 Video: RCA x 1 or BNC x 1, S-VIDEO (4pin) x 1 or S-VIDEO Y/C (BNC), Video Audio: RCA (L/R) x 2
Output terminals	RGB: Min D-Sub 15 pin x 1, Audio: Stereo mini jack (φ3.5mm) x 1 (Variable Out)
Communication terminals	LAN (RJ-45): x 1 (Projector control), RS-232C: D-Sub 9pin x 1 (Direct command is available.), USB: x 1 (for Mouse Cursor Control), Wired remote (IN): x 1 (φ3.5mm Stereo mini jack), Wired remote (OUT): x 1 (φ3.5mm Stereo mini jack)
Audio speaker	10W Mono
Dimensions (W x H x D)	17.4 x 8.1 x 17.1 inch (Including Detachable Terminal Cover)
Weight	9.8kg / 21.6lbs (Excluding Detachable Terminal Cover)
Power supply	AC100 - 240V, 50/60Hz
Accessories	Replacement Lamp (VLT-XL6600LP), Optional Lens: OL-X500SZ, OL-X500LZ, OL-500TZ, OL-X500FR(F), Hard shell rolling case: XL7000-ATAC, Ceiling Mount: XL5950CM
Warranty	3-Years Parts/Labor, 3-Years Express Replacement Assistance, 1-Year or 500 hours lamp warranty (whichever comes first)


• Compliance with ISO21118-2005  
 • All brand names and product names are trademarks, registered trademarks or trade names of their respective holders.  
 • Lamp life specification is an estimate based on information provided by the lamp manufacturer and is not the duration of the warranty. Lamp will shut-off automatically when usage reaches the specified estimated maximum lamp hours.

### Projection Distance with Optional Lenses

Screen Size (inch)	OL-X500SZ		OL-X500LZ		OL-X500TZ		OL-X500FR			
	Shortest (Wide)		Longest (Tele)		Shortest (Wide)		Longest (Tele)			
	inch	m	inch	m	inch	m	inch	m		
60	74	1.9	90	2.3	-	-	-	-	41	1.0
80	100	2.5	121	3.1	161	4.1	228	5.8	357	9.1
100	125	3.2	152	3.9	203	5.2	286	7.3	448	11.4
150	189	4.8	229	5.8	307	7.8	432	11.0	675	17.1
200	253	6.4	305	7.8	411	10.4	577	14.7	902	22.9
250	317	8.1	-	-	515	13.1	722	18.4	1129	28.7

### Screen Size and Projection Distance

Refer to the following table to determine the screen size and projection distance.



Diagonal size	Screen Size				Projection distance (L)				Lens movable range						
	Height (H)		Width (W)		Shortest (Wide)		Longest (Tele)		H1		H2		W1		
	inch	cm	inch	cm	inch	m	inch	m	inch	cm	inch	cm	inch	cm	
60	152	29	75	52	133	104	2.6	133	3.4	15	38	4	10	3	7
80	203	39	100	70	177	140	3.5	178	4.5	20	51	5	13	4	9
100	254	49	125	87	221	175	4.5	223	5.7	25	63	7	17	4	11
150	381	74	187	131	332	264	6.7	336	8.5	37	94	10	25	7	17
200	508	98	249	174	443	354	9.0	449	11.4	49	125	13	34	9	22
250	635	123	311	218	553	443	11.2	-	-	62	156	17	42	11	28

\* The above figures are approximate and may be slightly different from the actual measurements.

# MITSUBISHI ELECTRIC

## MULTIMEDIA DATA/VIDEO PROJECTORS


More venues. More applications.

Presenting the 1080p, 5000lm Projector



**FULL HD 1080** **5000lm**  
HIGH BRIGHTNESS

MITSUBISHI DIGITAL ELECTRONICS  
 AMERICA, INC.  
 Presentation Products Division  
 Phone: 888.307.0349  
 www.mitsubishi-presentations.com



MITSUBISHI ELECTRIC SALES  
 CANADA, INC.  
 Display & Imaging Solutions Division  
 Phone: 905.475.7728  
 www.mitsubishielectric.ca

New FL7000U

Present in impressive full1080p high-definition,  
 complete with split (side-by-side) screen display.  
 Vividly reproduce your presentation and video images in brilliant 5000lm  
 for videoconferences, seminars, lectures and meetings.  
 With the FL7000U your power of expression is a cut above the rest  
 and is a key to persuasive presentations every time.

# projector that's ideal for you.

Visual communications that's a step ahead

*New*



### Super bright 5000lm

The FL7000U delivers super bright 5000 lumen images. A high brightness level for presenting in large meeting rooms and conference halls.




### Ultra Quiet 29dBA Operation

Fan noise emanating from a projector can get annoying during a presentation or videoconference, but now that's a thing of the past. The FL7000U offers a significantly low noise level of only 29dBA (low lamp mode). As a result, your audience can enjoy the presentation or conference without noisy distractions from the projector.

### Long 4000hrs Lamp Life

Designed with a lamp temperature controlling system, the FL7000U can support an estimated lamp life of up to 4000 hours\*1. The long life lamp makes dramatic reductions in overall cost of ownership by decreasing the frequency of lamp replacements.



(\*1): When used in Lamp Low mode. Maximum lamp life at standard mode use is 2,000 hours. (\*2): Lamp life refers to the average time required for brightness to be reduced by half, and not the time specified in the warranty. Use time may vary widely by the environment and conditions, and whether or not cleaning and other maintenance procedures are followed. Lamp will shut-off automatically when usage reaches the specified estimated maximum lamp hours.

