

AG-DVX100

1/3" IT-3CCD MiniDV Camcorder with recording rate of 25-fps

MiniDV



NEW

With its frame rate of 25 frames per second, the new MiniDV Camcorder AG-DVX100 is the first in its class to offer recording technology ideal for film-like shooting.



STANDARD ACCESSORIES

- AC adaptor
- Charger
- Shoulder strap
- AC cable
- DV cable
- Large eye cap
- Lens cap
- Battery (1.6 Ah)
- Wireless remote controller
- Cleaning tape
- User's manual

OPTIONAL ACCESSORIES

- | | |
|-----------|---------------------------|
| AG-B15 | AC adaptor |
| AG-LW4307 | 0.7x wide conversion lens |
| CGR-D08 | Battery pack (0.8 Ah) |
| CGR-D16 | Battery pack (1.6 Ah) |
| CGR-D28 | Battery pack (2.8 Ah) |
| QR-DVC10 | Anton Bauer plate |
| VW-CD1 | IEEE1394 cable |
| VW-VMS2 | Stereo microphone |

GENERAL SPECIFICATIONS

- | | |
|--------------------|--------------------------------------|
| Power requirements | DC 7.2 V |
| Power consumption | 6 W |
| Weight | 2 kg / 4.4 lb
(fully operational) |

CAMERA FEATURES

- Three 1/3" 480,000 pixel IT CCD image sensors (interlace and progressive scan)
- Recording rate of 25-fps
- Wide angle lens F32.5 - 325 mm / 1.3" - 12.8" with optical 10x zoom
- Digital zoom functions
- 2,000 lux sensitivity at f11
- Electronic stabilizer
- Gain of up to +18 dB
- ATW (automatic tracing white) balance
- 0.44" electronic viewfinder
- 3.5" LC display (200,000 pixel)
- Manual and automatic focus
- Manual and automatic iris
- Two optical ND filters

VTR FEATURES

- Digital component recording (MiniDV)
- Recording time of 83 minutes with MiniDV cassette
- PCM audio recording
- Complete drive functions
- Manual audio level control
- Microphone in (XLR), 2 CH
- Microphone connection with phantom power supply (48 VDC on/off)
- Digital in/out IEEE1394 (4-pin)
- Composite out (RCA)
- Y/C out (4-pin)
- Audio out (RCA L/R)