

System	RH25D(Head) + RT30B(Tripod) + SP-2B(Floor spreader) + RC-30(Carrying case)		
Payload	6 kg / 13 lb	Tilt angle	+90° / -70° (Limited to ±40° with maximum counterbalance.)
Weight	6 kg / 13.2 lb	Pan angle	360°
Height	① H : 1660 mm W : 710 mm (※Reference)	Counterbalance	Range : 1.8 kg-5 kg / 4-11 lb (CG100 mm)
	② H : 560 mm W : 1105 mm (")		System : Continuous
Folded length	③ L : 855 mm (")	Drag mode	2STEP
Camera plate (Sliding range)	Sliding plate ±40 mm / ±1.6"	Ball diameter	∅75 mm
Plate attachment (Screw sliding range)	Type: 1/4-20UNC screw with video pin	Section	2STAGE (Material: Aluminum)
	76 mm / 3"	Tripod fixation	Fixing lock knob
Spare screw	Type: 1/4-20UNC , 3/8-16UNC screws	Spreader	SP-2B (Telescopic, Removable)
	Equipped on the top of the head (beneath sliding plate)	Pan handle	PH-6B
		Case material	Nylon, EVA, PU, PP, POM

Remarks

■ Exterior Dimensions (mm)

