

Invented in 1982, their unique patented construction and design have won these large lightweight softboxes worldwide popularity. A lightweight die cast rigid central mounting for the flashhead inside the unit, which places the flashtube at the point of focus. The optical result is a light source, which is so even at the diffuser surface, that many famous photographers use the Octa as a single light source for portrait photography. In the U.S.A. it is often referred to as "The Beauty Light". This exceptional softness of the light has sold many of thousands of units, adapted to other flash systems which do not have equivalent light sources.

Indirect Lights Advantages

- Super fast to set up, with the unique EL folding construction.
- 360° rotating system.
- All Indirect Light Banks are supplied with a Carrying Bag.
- Accepts BXRI or Style RX compact flashes, which can be easily controlled with the EL-Skyport Remote and Trigger System.
- Accepts all Elinchrom flashheads including the Ranger Quadra Heads, with Adapter Ring 26339.



Product with diffuser



EL-Octa 190 cm

code N° 26158

360° rotating system, incl. diffuser and carrying bag. Does not include flashhead and tripod.



EL-Quadra 145 x 145 cm

code N° 26156
360° rotating system, incl.
diffuser and carrying bag. Does
not include flashhead and tripod.

EL-Recta 72 x 175 cm

code N° 26154
360° rotating system, incl.
diffuser and carrying bag. Does
not include flashhead and tripod.



EL-Strip 33 x 175 cm

code N° 26158
360° rotating system, incl.
diffuser and carrying bag.
Does not include flashhead
and tripod.



Rotalux Deep Indirect

This new design is based on the Rotalux softbox range and accepts an indirectly, internally fitted flash unit.

This design offers a superb crispy light, when used without diffuser and can be modified to a soft light with softer shadows by using the included diffuser. All Fashion / Beauty images in this brochure are photographed with the new Rotalux Deep 150.

Included is a carrying bag and the external diffuser. The indirect light bank folds down like the Rotalux softboxes and can be easily transported.

The Facts

- Diameter 150 cm
- Depth 73 cm / total depth with tilt head and handle 96 cm
- 360° revolving system with screw locking
- Including carrying bag and external diffuser
- Optional available Hooded Diffuser // 26771
- Requires the EL-Tripod 31043 or heavier

Rotalux Deep Indirect 150 cm

code N° 26188
incl. standard diffuser and carrying bag.

Hooded Diffuser (optional)

code N° 26771



EL - Set Cases



EL - Compact Case | code N° 33209

New modern look with ergonomic carrying handle and locking system. Carries and protects three compact flashes Style RX 300, 600, 1200 or Elinchrom flashheads. 63.5 x 46 x 20.5 cm, 4.75 kg

Pro Basic Set | code N° 20767

Sync cord 11075

Reflector 16 cm 26143

Reflector 18 cm 26144

Umbrella translucent 85 cm 26371

Umbrella white 85 cm 26372

EL-Compact Case 33209

Carrying bag 33220



EL - Power Pack Case

code N° 33215

For all Digital RX packs, all Ranger RX models and 1-2 flashheads.



EL-Tube Bag BXRi | code N° 33199

Carry and protects two BX-Ri 250 / 500

EL-Tube Bag D-Lite-it | code N° 33198

Carry and protects two D-Lite-it 200 / 400



EL-Skyport Hard Shell Case | code N° 33000

EL - Tables

The EL Multi -Table is a flexible creative tool for universal Table-Top shootings. The latest design is a robust, ultra stable aluminium profile construction and is very easy to setup. The EL Multi Table offers variable radius curves with amulti-angle, adjustable height-shooting surface. A secondary transparent shooting surface enables heavier objects to be photographed without the surface deforming. An optional, additional tray can be mounted for reflective or transmitted lighting effects.



EL Multi-Table Complete

code N° 19228

Includes a Plexiglas plate white, matt / glossy 80 x 200 cm / 7.5 kg & transparent Plexiglas plate 80 x 100 cm / 11.5 kg



19228 + 19226

EL Multi-Table | code N° 19227

without plexiglas plates.

EL Multi-Table additional tray | code N° 19226

Including plexiglas plate transparent 80 x 100 cm for second shooting surface.

EL Multi-Table additional tray | code N° 19225

Without plexiglas plate.

Plexiglas plate white | code N° 26265

Matt/glossy 200 x 80 cm

Plexiglas plate transparent | code N° 26267

80 x 100 cm

EL Computer-Table | code N° 22901

The Computer Table supports 13", 15" and 17" Laptops and is a useful studio accessory for digital imaging.

The base is made of metal and includes the tilt-head, which fits to any standard tripod with 16 mm spigots.

To ensure best possible stability and drop down security, the EL-Tripod 31043, or heavier is required.

- Dimensions: width: 50 cm, depth: 28 cm
- Weight including tilt-head 1.5 kg
- Supports Laptops up to 40 cm x 27 cm / 3.5 kg





EL-Sync Cord 5m | code N° 11088

Camera pc > 3.5 mm jack
EL units with 3.5 mm sync plug: Style, Style S, Style RX, FX, BX, Chic 1/2, Digital 1/2, Digital RX 1200/2400, D-Lite, D-Lite-it, BXRI.



EL-Sync Extension Cord 10m | code N° 11080

EL-Amphenol female > male
To extend following sync cords: 11075, 11074, 11089, 11081, 11083, 11072.



Sync Cord Transmitter 20 cm | code N° 11120

Camera pc > 2.5 jack
This cable connects the EL-Skyport Transmitter or the Prolinca IR-Transmitter with the camera PC socket.



EL-Sync Cord 2m | code N° 11084

Camera pc > 3.5 mm jack
EL units with 3.5 mm sync plug: Style, Style S, Style RX, FX, BX, Chic 1/2, Digital 1/2, Digital RX 1200/2400, D-Lite, D-Lite-it, BXRI.



EL-External Photocell with clamp 5m

code N° 11081
EL-Amphenol > photocell
A photocell mounted on a clamp with 5 m sync cable and standard EL-Amphenol plug for EL flash units, except Style FX, BX, D-Lite, D-Lite-it, BXRI. To be used when the master flash is too far or even hidden from the built-in photocell. Style FX, BX, D-Lite, D-Lite-it and BXRI.



Sync Adapter 3.5-PC | code N° 11126

The Sync Adapter 3.5 mm - PC (female) connects the EL-Skyport Universal Speed Receiver with any other PC (male) sync plug.



EL-Sync Cord 5m | code N° 11075

Camera pc > EL-Amphenol
Elinchrom standard sync cord for all self-contained (compact) flash units and power packs. Except Style FX, BX, D-Lite, D-Lite-it and BXRI.



Sync Adapter 6.2 - 3.5 J | code N° 11125

Sync Adapter 6.2 - 3.5 j. This device converts 6.2 sync plugs to 3.5 mm standard sync sockets. The Sync Adapter is part of the EL-Skyport Universal Set 19360.



EL-Spiral Sync Cord 5m | code N° 11074

Camera pc > EL-Amphenol
Gold plated contacts to increase the connectivity, with a flexible spiral section, for all EL compacts and power packs. Except Style FX, BX, D-Lite, D-Lite-it and BXRI.



EL-Sync Adapter 6.35 phone jack 10 cm

code N° 11083
EL Amphenol > 6.35 phone jack female
To connect sync cords with 6.35 phone jack. Except Style FX, BX, D-Lite, D-Lite-it and BXRI.



EL-FRC Sync Cable-Receiver 50 cm

code N° 11072
EL-Amphenol male > 2.5 jack
This cable connects the FRC Receiver 19316 with the EL flash unit. Except Style FX, BX, D-Lite, D-Lite-it and BXRI.



EL-Sync Hardwire Cord 5 m | code N° 11089

3.5 mm jack > EL-Amphenol
To hardwire units in case the photocell has a bad reception due to long distance between flash units. For all self-contained (compact) flash units and power packs. Except Style FX, BX, D-Lite, D-Lite-it and BXRI.



Sync Cord Transmitter 50 cm | code N° 11071

Camera pc > 2.5 jack
To connect the EL-Skyport Transmitter, or the FRC Transmitter with the camera pc.



Sync Cord Transmitter 30 cm

code N° 40203 Cord
Camera pc > 2.5 jack
This cable connects the EL-Skyport Transmitter or the Prolinca IR-Transmitter with the camera PC socket.

Halogen Lamp Adapter

code N° 23101
Converts from E 27 to a GX 6.35 socket. For EL-Compacts: EL 250 / 500, Style Compacts, former Flashheads EL-S, EL -T and actual Mini S / A Heads. Note: Once the adapter is fitted use only with the following lamps: For Compacts 23034, for Flashheads 23022 or 23005.



Prolinca IR-Transmitter | code N° 40203

